

Serial No. 10/804,438
60130-1976
04ARM0082

IN THE SPECIFICATION:

Please amend the specification as follows:

- [25] The curtain assembly 24 includes a soft canvas and clear plastic window ~~28~~29 mounted over a frame 30. The curtain assembly 24 is primarily of a soft construction. The frame 30 defines attachments 31 to secure the curtain assembly 24 to the lower door assembly 14.
- [26] The lower door assembly 14 generally includes an inner panel 32 and ~~an~~ a door outer panel 34 mounted to the frame 18. The frame 18 defines a cavity 36 which receives one of the upper door assembly 16 along an open edge 38. A front face 40 and a rear face 42 of the frame 18 includes fastener apertures 44a-d, to receive a fastener 46 such as a bolt (Figure 3). Preferably, the bolt heads are exposed along the faces 40, 42 for access and aesthetic reasons.
- [28] The hinged trim portion 50 is defined by a trim hinge 52 which is generally parallel to the open edge 38. The trim hinge 52 is preferably a living hinge which permits the trim portion to pivot about the trim hinge 52 (illustrated by arrow H). By pivoting the hinged trim portion 50 away from the open edge 38, the cavity 36 is readily exposed for passage of the door cassette 22 and any associated components such as the window drive arrangement 28.
- [29] The glass window 26 and the soft canvas and clear plastic window assembly ~~28~~29 are of generally the same thickness but the drive arrangement 28 required to guide and move the glass window 26 is significant thicker. This difference in thickness is accommodated by pivoting of the hinged trim portion 50 to permit passage of the thicker components.
- [34] A seal 60 extends from the reinforcement structure 54. The seal 60, once the trim portion is secured, rides against the glass window ~~glass~~-26 to provide a seal for the cavity

Serial No. 10/804,438
60130-1976
04ARM0082

36. A fixed seal 62 extends from the door outer panel 34. The glass window glass-26 is |
movable therebetween.
